

## 71234 series with fixed stem collector bottle

- Lightweight tool
- Toughened plastic body and heavy duty rubber base
- Quick release stem collector bottle (71233 series)
- Fixed stem collector bottle (71234 series)
- Adjustable vacuum air flow
- Enhanced tool life
- Soft touch rubber grip on handle
- Integral cycle counter

- Reduces operator fatigue
- High placement speed
- Robust tool
- Minimized air consumption
- Reduced time to empty stem collector
- Places a wide range of lockbolts & breakstem fasteners
- Ergonomic

Weight (min. with equip.)	2.3 kg (5.1 lbs)
Pull force @ 5.5 bar	18.68 kN (4200 lbf)
Stroke (min.)	17 mm (0.67 in)
Cycle time (approx.)	1.2 sec
Air supply pressure	5-7 bar (80-100 psi)
Free air volume @ 5.5 bar	4.3 litres
Noise level	<75 dB(A)
Vibration	<2.5m/s <sup>2</sup>

Up to 6.4mm (1/4") breakstem rivets produced by Avdel except Monobolt® and Interlock® structural rivets.

Avseal® II sealing plugs up to 12 mm

Avtainer® lockbolts 10.0 mm (3/8")

Avdelok® and Maxlok® lockbolts 4.8 mm (3/16")  
and 6.4 mm (1/4")

Hemlok® structural rivets 6.4 mm (1/4")

## Avibulb® XT and Avinox® XT structural rivets

For detailed information on placing capability and nose equipment please refer to the tool manual on our website [www.avdel-global.com](http://www.avdel-global.com) or contact your local Avdel representative.

